



⊕ Security


Dual MCUs

Individual MCU for each inside and outside circuits,
Double protection from division and cooperation



Strong Encrypted Door Card

CPU Embedded card with Siemens exclusive
encryption algorithm,
Anti-cloning by individual identity



Semiconductor Fingerprint Sensor

192 super resolution fingerprint sensor tailor
made by FPC,
Gun safe level identification algorithm




Strong Encrypted Door Card

CPU Embedded card with Siemens exclusive
encryption algorithm,
Anti-cloning by individual identity



Class C Security Level Cylinder

Cylinder in tortoise with sensor,
Time alarm to prevent technology opening




PIN Code with Imaginary Number

Up to 20 bytes length with imaginary numbers,
Prevent PIN exposed, touch pad fingerprint
residue resistant



Kid Lock

Prevent technic opening with peep hole tools,
Protect kids from accidentally opening the door.



⊙ Humanity

Handle with Bearings

Handle equipped with 4 bearings both inner and
outer
Flipping smoothly and prevent handle hang down



Multiple Unlock Methods

Fingerprint, password, encrypted ID card and key,
Easy to use, quick to start for all user types




Status Alert

Alert for unlatched lock status,
Alert for low power status



Door Bell Integrated

Door bell embedded inside door lock,
Excellent speaker chamber design



Voice Menu

Menu voice from real human,
Easy to configure



Emergency Power Supplier

Hidden micro-USB Interface,
Low power emergency carefree



Thumbturn

2 steps to effect (press then rotate),
Prevent kids from accidentally locking inside



Siemens Smart Door Lock C320


Product Size : 392x80x28.5mm (Lever Not Included)	AVS Hotline : 400-821-5192
Component : Exterior body, Interior body, Mortise, AA Batteriesx8, Cylinder,	Website : www.siemens.com.cn/smartlock
Installation template, User Manual, Accessories, Keysx2, CPU Cardsx2	Manufacturer : Siemens Ltd., China
Power Supply : AA Batteries, Micro USB charging for Emergency	Address : No. 7, Wangjing Zhonghuan Nanlu,
Users Capacity : Fingerprint 100, PIN 50, CPU Cards 10	Chaoyang, Beijing, PRC
Standard : GB21556-2008	
Working Temperature : -25°C ~ 70°C	
Working Humidity : 20% RH ~ 90% RH	



Security


Stainless Steel Front Panel

Entire front panel made from 2mm thick 304 stainless steel,
High strength protection, drilling resistant, striking resistant



Faraday Cage

Electromagnetic interference Shielding
Strong protection for core PCB circuit inside



Dual MCUs

Individual MCU for each inside and outside circuits,
Double protection from division and cooperation



Strong Encrypted Door Card

CPU Embedded card with Siemens exclusive encryption algorithm,
Anti-cloning by individual identity




Semiconductor Fingerprint Sensor

192 super resolution fingerprint sensor tailor made by FPC,
Gun safe level identification algorithm



Class C Security Level Cylinder

Cylinder in tortoise with sensor,
Time alarm to prevent technology opening



PIN Code with Imaginary Number

Up to 20 bytes length with imaginary numbers,
Prevent PIN exposed, touch pad fingerprint residue resistant



Humanity

Handle with Bearings

Handle equipped with 4 bearings both inner and outer
Flipping smoothly and prevent handle hang down



Multiple Unlock Method

Fingerprint, password, encrypted ID card and key,
Easy to use, quick to start for all user types



Status Alert

Alert for unlatched lock status,
Alert for low power status




Door Bell Integrated

Door bell embedded inside door lock,
Excellent speaker chamber design



Voice Menu

Menu voice from real human,
Easy to configure



Emergency Power Supplier

Hidden micro-USB Interface,
Low power emergency carefree



Thumbturn

2 steps to effect (press then rotate),
Prevent kids from accidentally locking inside



Siemens Smart Door Lock C321

Product Size : 400×80×29mm (Lever Not Included)	A/S Hotline : 400-821-5192
Component : Exterior body, Interior body, Mortise, AA Batteries×8, Cylinder,	Website : www.siemens.com.cn/smartlock
Installation template, User Manual, Accessories, Keys×2, CPU Cards×2	Manufacturer : Siemens Ltd., China
Power Supply : AA Batteries, Micro USB charging for Emergency	Address : No. 7, Wangjing Zhonghuan Nanlu,
Users Capacity : Fingerprint 100, PIN 50, CPU Cards 10	Chaoyang, Beijing, PRC
Standard : GB21556-2008	
Working Temperature : -25°C ~ 70°C	
Working Humidity : 20% RH ~ 90% RH	